

# redo::lyser



redo::lyser monitors ORP and temperature

redo::lyser pro: high temperature range

- s::can plug & measure
- measuring principle: unique, non-porous / non-leaking combined reference electrode for technically unrivalled and consistend ORP performance
- multiparameter sensor
- ideal for surface water, ground water and drinking water, also waste water
- long term stable and maintenance free in operation
- factory precalibrated
- mounting and measurement directly in the media (InSitu) or in flow cell
- operation via s::can terminals & s::can software
- plug connection or fixed cable

## recommended accessories

| part number  | article name                                 |
|--------------|--|
| D-330-xxx    | con::cube V3                                 |
| D-320-xxx    | con::lyte                                    |
| F-12-sensor  | carrier s::can physical probes               |
| F-48-sensor  | s::can Sensor flow-cell (by-pass setup), PVC |
| S-11-xx-moni | moni::tool Software                          |



#### technical specification

|                               |   |                                 |  |
|-------------------------------|---|---------------------------------|--|
| measuring principle           | potentiometric  | weight (min.)                   | 400 g  |
| measuring principle detail    | combined, non-porous reference electrode              | dimensions (Ø x l)              | 33 x 257 mm  |
| resolution                    | 1 mV  | operating pressure              | 0 ... 10 bar   |
| accuracy (standard solution)  | +/- 10 mV   | installation / mounting         | submersed or in a flow cell                                |
| response time (T90)           | 30 ... 0 sec.   | process connection              | quick connect  |
| integrated temperature sensor | 0 ... 90 °C   | flow velocity                   | 0.01 m/s (min.)<br>3 m/s (max.)                            |
| integration via               | con::lyte<br>con::nect                                | automatic cleaning              | media: compressed air<br>permissible pressure: 3 ... 6 bar |
| power supply                  | 9 ... 18 VDC  | storage temperature (electrode) | -5 ... 30 °C   |
| power consumption (typical)   | 0.8 W   | storage temperature (sensor)    | -10 ... 60 °C  |
| power consumption (max.)      | 1 W   | conformity - EMC                | EN 61326-1   |
| interface to s::can terminals | sys plug (IP67), RS485                                | conformity - safety             | EN 61010-1   |
| cable length                  | 7.5 m fixed cable (-075) or<br>plug connection (-000) | operating temperature (eco)     | 0 ... 70 °C  |
| housing material              | stainless steel 1.4404/1.4401,<br>POM-C               | operating temperature (pro)     | 0 ... 90 °C  |
|                               |   | protection class (-000)         | IP67   |
|                               |   | protection class (-075)         | IP68   |

#### measuring range

|                             |      | parameter  |                  |                    |
|-----------------------------|------|------------|------------------|--------------------|
|                             |      | redox [mV] | temperature [°C] | part number        |
| redo::lyser eco (ORP, temp) | min. | -2000      | 0                | E-513-2-000 / -075 |
|                             | max. | 2000       | 70               |                    |
| redo::lyser pro (ORP, temp) | min. | -2000      | 0                | E-513-3-000 / -075 |
|                             | max. | 2000       | 90               |                    |